



PRODUZIONE E LAVORAZIONE
RETI METALLICHE ELETTROPUNTATE

WELDED MESH FOR FLOORS

Possible uses: laying glue on the screed or existing floors

<i>Mesh mm</i>	12 x 24	
<i>Wire diameter mm</i>	0,65	Steel Wire Galvanized before welding
<i>Weight Kg/m²</i>	0,310 ~	
<i>Section mm²</i>	26 13	Cross wire (in 100 cm)
<i>Tensile strenght Kg/m²</i>	400 ~ 200 ~	Longitudinal (in 100 cm)
<i>Coeff. dilatazione termica α</i>	11,8 ~	0° - 100°
<i>Coeff.of thermal expansion α</i>	Panels dim. 100 x 50 cm/each.	
	Carton box with 15 unit of 50 pcs	

Some data show in the comparative lists can be rounding up or down and consequently are not absolute



**PRODUZIONE E LAVORAZIONE
RETI METALLICHE ELETTROPUNTATE**

WELDED MESH FOR FLOORS

The use of our welded mesh regulates and distributes the tension, conferring monolithic and ductility whole glue-tiles so as to prevent cracks, crazing and peeling.

INSTALLATION

- Place the mesh on the old floor, combining the various panels.
- Apply the enough glue to cover well the entire welded mesh.
- Install the floor.

