

FILTRATION

GALVANIZED WIRE BEFORE WELDING

Mesh	Wire	Width	Roll Lenght	Open Area
		Min / Max		
	Ø mm	mm	m	%
8 x 8*	0.65	77 ÷ 800	50	84
12 x 12	0.65	77 ÷ 1200	50 - 100	89
12 x 12	0.80	77 ÷ 1200	50	87
12 x 12	1.00	77 ÷ 1200	35	84
12 x 24	0.65	77 ÷ 1200	50 - 100	92
12 x 24	0.80	77 ÷ 1200	50 - 75	90
16 x 16	0.80	100 ÷ 1200	50	90
16 x 16	1.00	100 ÷ 1200	35 - 50	88
16 x 16	1.20	100 ÷ 1200	30	86
24 x 24	0.80	100 ÷ 1200	50 - 80	93
24 x 24	1.40	100 ÷ 1200	25	89
50 x 24*	0.65	1000	150	96

STAINLESS STEEL AISI 304

Mesh	Wire	Width	Roll Lenght	Open Area
		Min / Max		
	Ø mm	mm	m	%
12 x 12	0.70	1000	50	89
12 x 12	0.80	585 ÷ 1000	50	87
12 x 24	0.80	585 ÷ 1000	50	90
24 x 24	0.60	1000 ÷ 1200	50	95
24 x 24	0.80	1000 ÷ 1200	50	93
24 x 24	1.00	1000 ÷ 1200	25	92

* non-standard mesh

Some data show in the comparative lists can be rounding up or down and consequently are not absolute